

Model 3200 Semi Mounted Moldboard Plow



THE ONLY TRUE HIGH RESIDUE PLOW

- 3 - 5 Bottoms
- On Land tail wheel (11L x 15 tire)
- Mechanical steering
- Auto reset (mechanical or hydraulic)
- Spring loaded coulter / 20" blades
- Manual Adjust 14" - 20"
- Main beam 6" x 8"
- Underbeam clearance 35"
- Fore/Aft clearance 40"
- Cat. #2 or #3 hitch pins

SPECIFICATIONS

Model	Size	Approximate Weight
3203	3 Furrow	2160 lbs.
3204	4 Furrow	2880 lbs.
3205	5 Furrow	3600 lbs.

STANDARD FEATURES

- Mechanical steering
- Manual adjustable furrow width 14" - 16" - 18" - 20"
- On-land tail wheel (11L x 15" tire)
- Under-beam clearance - 35"
- Fore-aft Clearance - 40"
- 20" Rippled spring loaded coulter
- Double spring auto reset or hydraulic reset
- Cat. #2 or #3 hitch pins
- Main frame 6" x 8" tubular steel
- All cylinders & hoses to tractor
- Field ready

OPTIONS

- Lead Furrow Hydraulic Cylinder
- Coverboards

SALFORD PLOW BOTTOMS



SALFORD
S8 BOTTOM



SALFORD
IH STYLE BOTTOM



CONSERVATION
TILLAGE BOTTOM
(Mini-Moldboard)

3 YEAR LIMITED WARRANTY

Salford Tillage Products are designed and built with longevity and serviceability in mind and are intended to withstand the normal rigors of agricultural use.