

Model 4200 Moldboard Plow,



THE ONLY TRUE HIGH RESIDUE PLOW

- 3 - 8 Bottoms
- Manual Adjust 14" - 20"
- Industry leading underbeam clearance 35"
- Auto reset (mechanical spring or hydraulic)
- Hydraulic rear wheel steering

SPECIFICATIONS

Model	Size	Approximate Weight
4203	3 Furrow	2550 lbs.
4204	4 Furrow	3280 lbs.
4205	5 Furrow	4100 lbs.
4206	6 Furrow	5188 lbs.
4207*	7 Furrow	6132 lbs.
4208*	8 Furrow	7008 lbs.

*Bridged main frame

STANDARD FEATURES

- Hydraulic steering
- In-Furrow tail wheel (14" x 17.5 TL lug tire)
- Gauge wheel Implement tire (optional lug tire)
- Manual adjustable plowing widths 14" - 16" - 18" - 20"
- Under-beam clearance - 35"
- Fore-aft clearance - 40"
- 20" spring loaded rippled coulter
- Double spring auto reset or hydraulic reset
- Cat. #2 or #3 hitch pins
- Main frame 8" x 8" tubular steel
- Draw frame 8" x 8" tubular steel
- Field ready with all cylinders & hoses to tractor

OPTIONS

- Lead furrow hydraulic cylinder
- Coverboards
- Lug Gauge Wheel

SALFORD PLOW BOTTOMS



SALFORD
S8 BOTTOM



SALFORD
IH STYLE BOTTOM



CONSERVATION
TILLAGE BOTTOM
(Mini-Moldboard)

3 YEAR LIMITED WARRANTY

Salford Tillage Products are designed and built with longevity and serviceability in mind and are intended to withstand the normal rigors of agricultural use.