

Model 450 Field Cultivator



RAISING FIELD CULTIVATOR STANDARDS TO A HIGHER LEVEL OF PERFORMANCE

- Choice of S-tine or C-shank models
- Single point depth control with fine adjustment
- Narrow transport width of 13ft

SPECIFICATIONS

ALL MODELS		6-BAR S-TINE MODELS					C-SHANK MODELS				
Working Width	# of Wheels	# of Tines		Trans. Width	Trans. Height	Approx. Weight (lbs.)	# of Tines		Trans. Width	Trans. Height	Approx. Weight (lbs.)
		4"	5"				7"	9"			
10'	4	31	25	10'4"	4'6"	3600	18	14	10'4"	4'10"	4100
12'	4	37	29	12'4"	4'6"	3600	20	16	12'4"	4'10"	4100
14'	4	43	35	14'4"	4'6"	4000	24	20	14'4"	4'10"	4600
17'	6	53	43	13'0"	6'10"	4900	30	24	13'8"	7'5"	5600
19'	8	59	47	13'0"	7'10"	5300	34	26	13'8"	8'5"	7000
21'	8	63	51	13'0"	8'10"	5400	36	28	13'8"	9'5"	6200
23'	8	69	55	13'0"	9'10"	5700	40	30	13'8"	10'5"	6500
25'	8	75	61	13'0"	10'10"	5800	44	32	13'8"	11'5"	6600
27'	8	81	65	13'0"	11'10"	6000	46	36	13'8"	12'5"	6800

*Base frame width: 10' ; approximately 5 to 6 h.p. required per foot

S-TINE

- 110 lbs tip pressure
- 12 x 45 mm premium S-tines
- 20" ground clearance
- Standard shovel 2 ¾" Ultra Blue goosefoot
- Optional 3" Super Gold shovel



HD C-SHANK

- 200-270 lbs tip pressure
- 24" ground clearance
- Replaceable nylon pivot bushing
- 7" - 9" shank spacing

STANDARD FEATURES

- Tandem transport wheels, rear mounted
- Wing tandems 19 - 27 ft models (17 ft single wheel on wings)
- Wing wheel adjusters
- 4000 lbs wheel hubs
- 5000 lbs tandem pivot bearing
- SMV sign, safety chain
- Stone carrier grate, transport lights
- 3" x 5" Mainframe tubing
- Choose from single or double clevis hitch
- Forward mounted wing wheels
- Front and rear jack stands
- Adjustable hitch leveling
- Hydraulic coupler storage
- Fine adjust single point depth control
- 11L x 15 tires
- Hydraulic self-leveling hitch on all models

OPTIONS

- Adjustable tow hitch (One man hook-up)
- Hydraulic lines and quick coupler to tow hitch
- **Wide selection of Salford harrow attachments**

3 YEAR LIMITED WARRANTY

Salford Tillage Products are designed and built with longevity and serviceability in mind and are intended to withstand the normal rigors of agricultural use. Please talk to your **dealer** or call us today at +1 (519) 485-1293 for all the details.