

Model 6200 Hydraulic Vari-Width Moldboard Plow



THE ONLY TRUE HIGH RESIDUE PLOW

- 4 - 8 Bottoms
- Hydraulic width adjust 12" - 20"
- Industry leading underbeam clearance 35"
- Auto reset (mechanical spring or hydraulic)
- Hydraulic rear wheel steering

SPECIFICATIONS

Model	Size	Approximate Weight
6204	4 Furrow	3384 lbs.
6205	5 Furrow	4230 lbs.
6206	6 Furrow	5274 lbs.
6207*	7 Furrow	6314 lbs.
6208*	8 Furrow	7216 lbs.

*Bridged Main Frame

STANDARD FEATURES

- Automatic lead furrow adjuster
- Hydraulic steering
- Hydraulic adjustable furrow width 12" - 20"
- In-Furrow tail wheel (lug tire)
- Gauge wheel (11L x 15 tire)
- Under-beam clearance - 35"
- Fore-aft clearance - 40"
- 20" spring loaded rippled coulters
- Double spring auto reset or hydraulic reset
- Cat. #2 or #3 hitch pins
- Main frame 8" x 8" tubular steel
- Draw frame 7" x 7" tubular steel
- Field ready all cylinders & hoses to tractor

OPTIONS

- Lead furrow hydraulic cylinder
- Coverboards
- Lug Gauge Wheel

SALFORD PLOW BOTTOMS



SALFORD
S8 BOTTOM



SALFORD
IH STYLE BOTTOM



CONSERVATION
TILLAGE BOTTOM
(Mini-Moldboard)

3 YEAR LIMITED WARRANTY

Salford Tillage Products are designed and built with longevity and serviceability in mind and are intended to withstand the normal rigors of agricultural use.