

# Model 700 Field Cultivator



## RAISING FIELD CULTIVATOR STANDARDS TO A HIGHER LEVEL OF PERFORMANCE

- Choice of S-tine or C-shank models
- Single point depth control with fine adjustment
- Tandem axles on transport frame and wings
- 6 Bar frame - exceptional trash clearance

## SPECIFICATIONS

Size	# of Tines		# of "C"		Trans. Width		HP Req'd	Approx. Weight (lbs.)	# of Tires	# of Wing Cyl.	Trans. Height	
	4"	5"	7"	9"	S	C					S	C
40'*	121	97	69	54	19'	19'6"	210-250	9800	8	4	15'6"	15'10"
44'***	131	105	75	58	16'0"	16'8"	220-260	13900	12	8	13'6"	13'10"
47'***	139	111	79	62	16'0"	16'8"	235-280	14600	12	8	13'6"	13'10"
50'***	149	119	85	66	16'0"	16'8"	250-300	14900	12	8	13'6"	13'10"
62'***	185	147	105	82	19'0"	19'8"	310-400	20200	12	8	15'2"	15'6"

\* Single Fold  
 \*\* Bi-Fold Frame

## S-TINE

- 110 lbs tip pressure
- 12 x 45 mm premium S-tines
- 20" underbeam clearance
- Standard shovel 2 ¾" Ultra Blue goosefoot
- Optional 3" Super Gold shovel



## C-SHANK

- 200-270 lbs tip pressure
- 26" underbeam clearance
- Replaceable pivot bushing
- 7" - 9" shank spacing

## STANDARD FEATURES

- Tandem transport wheels, rear mounted
- Wing wheel adjusters
- 44' -50' Models: 8,000 lbs transport wheel hubs, 10,000 lbs transport frame pivot bearing
- 62' Models: 10,000 lbs transport wheel hubs, 16,000 lbs transport frame pivot bearing
- SMV sign, safety chain, stone carrier grate, transport lights
- Hydraulic self-leveling frame
- 4" x 6" Mainframe tubing
- Choose from single or double clevis hitch
- Forward mounted wing wheel tandems
- Front and rear jack stands
- Hydraulic coupler storage
- Fine adjust single point depth control

## OPTIONS

- "Land Hugger" floating frame with manual adjust caster wheels
- Adjustable tow hitch (One man hook-up)
- Hydraulic lines and quick coupler to tow hitch
- **Wide selection of Salford harrow attachments**

## 3 YEAR LIMITED WARRANTY

Salford Tillage Products are designed and built with longevity and serviceability in mind and are intended to withstand the normal rigors of agricultural use.