

Model 7200 On Land / In Furrow Semi-Mounted Plow



THE ONLY TRUE HIGH RESIDUE PLOW

- 6 - 8 Bottoms
- Manual adjust 14" - 20" (Optional hydraulic vari-width 12" - 20")
- Industry leading underbeam clearance 35"
- Auto reset (mechanical or hydraulic)
- On land / In furrow hitch

SPECIFICATIONS

Model	Total Number of Furrows
7206	6 Furrow
7207	7 Furrow
7208	8 Furrow

STANDARD FEATURES

- Manual adjustable plowing widths 14", 16", 18", 20"
- Hydraulic Steering
- In-Furrow Tail Wheel (14" x 17.5TL Lug tire)
- Gauge Wheel (Implement tire [Option - Lug tire])
- Lead Furrow Wheel (315 x 22.5 used truck tire)
- Optional - Hydraulic furrow width adjust
- Super HEAVY DUTY tubular frame construction
 - Main Frame 8" x 8" Tubular Steel
 - Draw Frame 8" x 8" Tubular Steel
- On Land / In furrow plowing
- Under-beam Clearance - 35"
- Fore-aft Clearance - 40"
- 20" Rippled spring loaded coulters
- Double spring auto reset or hydraulic reset
- Cat. #2 - #3 Hitch Pins
- Field Ready with all cylinders & hoses to tractor

OPTIONS

- Coverboards
- Hydraulic width Adjust
- Lug Gauge Wheel

SALFORD PLOW BOTTOMS



SALFORD
S8 BOTTOM



SALFORD
IH STYLE BOTTOM



CONSERVATION
TILLAGE BOTTOM
(Mini-Moldboard)

3 YEAR LIMITED WARRANTY

Salford Tillage Products are designed and built with longevity and serviceability in mind and are intended to withstand the normal rigors of agricultural use.