

Model 830 Disc Harrow



Staggered front gangs reduce ridging



Coil flex gang system for superior protection

SPECIFICATIONS

Cutting Width	Transport Width	# of Blades	HP Required	Solid Gang (approx. weight)	Coil Flex Gang (approx. weight)
7.5" BLADE SPACING					
11'0"	12'3"	34	50-75	3860 lbs	4100 lbs
12'3"	13'6"	38	55-80	4000 lbs	4240 lbs
13'6"	14'9"	42	60-90	4140 lbs	4382 lbs
9" BLADE SPACING					
11'4"	12'9"	30	50-75	3510 lbs	3759 lbs
12'9"	14'3"	34	55-80	3720 lbs	3960 lbs
14'3"	15'9"	38	60-90	3860 lbs	4100 lbs

*Rear Furrow Fillers not counted in # of discs

STANDARD FEATURES

- 22" x 3/16" (5mm) smooth blades
- Staggered front gangs
- HD adjustable scrapers
- Ratchet leveling front to rear
- All welded heavy wall tubular frame
- HD 1.5" diameter gang bolt
- Tongue jack
- 16" rear furrow fillers
- Adjustable gang angle 12° to 18° (front to rear)
- 7.5" or 9" blade spacing
- Large 5" diameter spools
- Step down discs for even soil surfaces
- Single 11L x 15 tires/wheels
- Weight/ft 310-320 lbs
- SMV sign, Safety chain, Hose holders

OPTIONS

- Dual 11L x 15 tires
- Tandem 11L x 15 tires
- Rear tow hitch hydraulics
- Rear tow hitch
- Coil flex gang system for rock or obstacle protection
- Mechanical self-leveling system
- Notched blades in lieu of smooth
- Large selection of easy mount leveling harrow
- Safety lighting
- 22" X 1/4" (6.5mm) blades

3 YEAR LIMITED WARRANTY

Salford Tillage Products are designed and built with longevity and serviceability in mind and are intended to withstand the normal rigors of agricultural use