

Model 850 Disc Harrow



SPECIFICATIONS

Size	# of Blades	HP Required	Solid Gang (approx. weight)	Coil Flex Gang (approx. weight)
7.5" BLADE SPACING				
15'*	52	75-110	6200 lbs	6600 lbs
17'*	56	85-120	7200 lbs	7600 lbs
18'2"*	58	95-135	7600 lbs	8000 lbs
19'5"	62	105-145	7800 lbs	8200 lbs
20'7"	66	110-150	8000 lbs	8400 lbs
21'10"	70	115-155	8200 lbs	8600 lbs
23'	74	120-160	8400 lbs	8800 lbs
9" BLADE SPACING				
15'*	42	75-110	5960 lbs	6290 lbs
17'*	46	90-125	6960 lbs	7160 lbs
18'5"*	50	100-140	7360 lbs	7560 lbs
20'	54	110-150	7560 lbs	7760 lbs
21'5"	58	115-155	7760 lbs	7960 lbs
23'	62	125-165	7960 lbs	8160 lbs

*Center-fold models
Rear Furrow Fillers not counted in # of discs

STANDARD FEATURES

- 22" x 3/16" (5mm) Smooth blades
- Choice of 7.5" or 9" spacing
- 11L x 15 wheels
- All hydraulic cylinders and hoses to tractor
- 1.5" round gang axles
- Choice of solid or coil flex gang system
- Single or double clevis
- Steel disc gang spools (5" diameter)
- Heavy duty solid scrapers
- Single point depth control adjuster
- Hydraulic self-leveling frame
- Safety chain, SMV sign, hose holders, safety lighting
- Tandems on mains and wings

OPTIONS

- Single 11L x 15 tires on wings in lieu of tandem
- Rear tow hitch
- Rear tow hitch hydraulics to tractor
- Rear tow hitch hydraulics to wing cylinders
- Notched disc blades in lieu of smooth
- 22" x 1/4" (6.5 mm) blades available
- Large selection of easy mount leveling harrows

3 YEAR LIMITED WARRANTY

Salford Tillage Products are designed and built with longevity and serviceability in mind and are intended to withstand the normal rigors of agricultural use.