

Model 860 HD Disc Harrow



A new choice for Primary Tillage
Salford's Coil Flex Gang System (patented) standard for superior protection
Mulch and incorporate residue and leave a level soil profile

Straight draft from our unique design



Center fold model

SPECIFICATIONS

Working Width	# of Blades	HP Required	Frame Configuration	Coil Flex Gang Weight	Weight per Ft.
9" BLADE SPACING 24" X 1/4" blades					
9'10"	26	80-100	Straight Frame	6100 lbs	630 lbs
11'4"	30	90-115	Straight Frame	6700 lbs	580 lbs
12'9"	34	100-130	Straight Frame	7100 lbs	550 lbs
14'3"	38	115-140	Straight Frame	7500 lbs	530 lbs
15'	42	120-150	Center fold	10,000 lbs	680 lbs
17'3"	46	140-170	Center fold	10,800 lbs	630 lbs
18'5"	50	145-185	Center fold	11,200 lbs	610 lbs
10.5" BLADE SPACING 26" X 1/4" blades					
9'11"	22	80-100	Straight frame	6200 lbs	620 lbs
11'6"	26	90-115	Straight frame	6700 lbs	580 lbs
13'3"	30	105-130	Straight frame	7200 lbs	550 lbs
15'	34	120-150	Center frame	10,000 lbs	680 lbs
16'8"	38	130-165	Center frame	10,600 lbs	640 lbs
19'4"	42	155-195	Center frame	11,500 lbs	600 lbs

STANDARD FEATURES

- All hydraulic cylinders & hoses to tractor
- 2 1/4" round gang axles, serviceable from both ends
- Single point depth control adjuster
- Hydraulic self leveling frame standard on center fold models
- Coil flex gang system (patented)
- Heavy duty solid scraper
- Safety chain, SMV sign, hose holders, safety lighting
- Rigid models: 4 11L x 15 walking tandems
- Wing Fold models: 4 11L x 15 tires highway service on mainframe, 2 11L x 15 tires on wing

OPTIONS

- Notched blades in lieu of smooth
- Optional 24" or 26" 8mm blade
- Adjustable rear tow hitch (one man hook-up)
- Rear tow hitch hydraulics
- Large selection of easy mount leveling harrows

3 YEAR LIMITED WARRANTY

Salford Tillage Products are designed and built with longevity and serviceability in mind and are intended to withstand the normal rigors of agricultural use.