

Model 870 HD Disc Harrow

A DUAL PURPOSE DISC FOR THE MOST DEMANDING CONDITIONS

Salford's coil flex gang system

Tandem wheels on main frame and wings

Over center transport folding

Large 4" x 6" main frame structure



SPECIFICATIONS

Working Width	# of Blades	HP Required	Transport Width	Transport Height	Weight (lbs)	Weight per Ft. (lbs)
7.5" BLADE SPACING 22" X 1/4" blades						
24'	78	130 - 170	13.5'	12'	15,400	640
26'8"	86	150 - 190	13.5'	13'	16,400	620
29'2"	94	190 - 230	13.5'	14'	17,300	600
31'8"	102	210 - 250	13.5'	15'	18,000	570
34'8"	110	225 - 275	16'	15'	19,300	540
9" BLADE SPACING 24" X 1/4" blades						
21'6"	58	120 - 215	13.5'	11'	15,400	720
24'8"	66	130 - 245	13.5'	12'	16,500	690
26'2"	70	140 - 260	13.5'	13'	16,900	650
28'8"	78	180 - 285	13.5'	14'	18,100	630
31'8"	86	200 - 315	13.5'	15'	19,300	600
35'	94	220 - 350	16'	15'	20,900	600
10.5" BLADE SPACING 26" X 1/4" blades						
23'	54	130 - 230	13.5'	12'	15,800	690
26'5"	62	140 - 260	13.5'	13'	17,000	650
29'8"	70	190 - 295	13.5'	14'	18,400	620
31'5"	74	200 - 315	13.5'	15'	19,200	610
34'8"	80	220 - 350	16'	15'	20,900	600

STANDARD FEATURES

- 1/4" (6.5 mm) Smooth Blades
- Highway Service tires on main frame
- All hydraulic cylinders and hoses to Tractor
- 2 1/4" round gang axles
- Coil flex disc gang mounts
- 15° Over center transport folding
- Steel disc gang spools
- Heavy Duty solid scrapers
- Single Point Depth Control Adjuster
- Safety Chain, S.M.V. sign, Hose Holders, Safety Lighting
- Single or Double clevis
- TANDEM 11L X 15 Tires on wings
- Gang bearings, all pivot mount, greaseable

OPTIONS

- Adjustable Rear Tow Hitch (One man hook-up)
- Rear Tow Hitch Hydraulics
- Notched blades in lieu of smooth
- LARGE selection of EASY MOUNT Leveling Harrows
- 5/16" (8mm) thickness available on select blade sizes

3 YEAR LIMITED WARRANTY

Salford Tillage Products are designed and built with longevity and serviceability in mind and are intended to withstand the normal rigors of agricultural use.