

9700 CTS (Conservation Tillage Specialist)



A NEW APPROACH TO PRIMARY TILLAGE

Works the entire soil profile.
 Unbeatable single pass performance.
 Working depth flexibility (4" - 14")
 Disc gangs have independent depth control

SPECIFICATIONS

Working Width	16" Shank Spacing				32" Shank Spacing		
	Number of Shanks	Avail. in Straight Gangs?	Avail. in Offset Gangs?	Approx. Weight	Number of Shanks	Approx. Weight	Frame Configuration
7' 6"	5	Yes	Yes	4,206 lbs	3	3,606 lbs	Straight Frame
9' 4"	7	Yes	Yes	5,889 lbs	4	4,989 lbs	Straight Frame
12' 0"	9	Yes	Yes	7,572 lbs	5	6,372 lbs	Straight Frame
14' 8"	11	Yes	Yes	9,255 lbs	6	7,755 lbs	Straight Frame
14' 8"	11	Yes	No	10,000 lbs	6	8,500 lbs	Wing Fold
17' 4"	13	Yes	Yes	10,937 lbs	7	9,137 lbs	Straight Frame
17' 4"	13	Yes	No	11,300 lbs	7	9,500 lbs	Wing Fold
20'	15	Yes	No	12,750 lbs	8	10,650 lbs	Wing Fold Only

STANDARD

- Equipped with SALFORD's unique Wide Sweep for complete ground shattering
- **Standard** chisel point 1" x 2 1/2" Reversible or Twisted Shovels
- **Auto Reset** Shanks / Adjustable trip-Average of 2600 lbs pressure
- **33" Underbeam** Clearance
- **Random** shank spacing (Maximum trash clearance)
- Fore/Aft distance **40"**
- **Large** Single Transport Wheels (22.5 rims)
- **Single Point Depth Control** Adjustment
- Safety Chain, S.M.V., Hose End Holders
- Safety Lighting

OPTIONS

- Gauge wheels
- Wider Floatation tires (5-7 shank machines)
- Machine available without disc gang
- New tire options (Standard machine equipped with used truck tires)
 - 5-7 shank (31.5 x 22.5)
 - 9-15 shank (42.5 x 22.5)
- Third trip spring for increased trip pressure in extreme conditions
- Notched Blades
- Wheel Mud Scrapers
- Shank and Point Options
 - Chisel Ripper
 - Parabolic Ripper
 - Straight Leg

DISC GANG SPECS. INCLUDE:

- **22" Notched or Smooth** Blades (1/4" / 6mm thick)
- **Disc Gang** Spring Cushioned
- **Steel** Spools
- **Hydraulic Depth Control**
- **Forward Pivot Point**
- **Mud Scrapers**
- **Offset gangs feature with curved blades**
- **Serviceable from both ends**

DISC SPACING

- 8" - Straight Blades
- 9" - Curved Blades

3 YEAR LIMITED WARRANTY

Salford Tillage Products are designed and built with longevity and serviceability in mind and are intended to withstand the normal rigors of agricultural use.